



D E C L A R A T I O N

I, Robert C. Ferber, declare that I am well qualified as a translator of German to English and that I have carefully reviewed the attached English language translation from the original document:

**Verfahren zum Regeln einer Sitztemperatur eines
Fahrzeugsitzes**

(Method for Adjusting the Temperature of a Motor
Vehicle Seat)

written in German; and that the attached translation is an accurate English version of such original to the best of my knowledge and belief.

I certify under penalty of perjury that the foregoing is true and correct.

Date 11/27/2006

Signature

Robert C. Ferber

Name

ROBERT C. FERBER



P036819/WO/1

DaimlerChrysler AG

Method for adjusting the temperature of a motor vehicle
seat

5

The invention relates to a method for adjusting the temperature of a motor vehicle seat according to the precharacterizing clause of patent claim 1.

10 One of the main objectives when designing a vehicle interior is to provide the occupant of a motor vehicle with optimum seating comfort. Special attention is directed here to the thermo-physiological comfort by regulating the transportation of heat and moisture. No
15 other component of the motor vehicle is in contact over such a large surface area and consistently with the occupant as the motor vehicle seat. Accordingly, a healthy and comfortable micro-climate is important between the seat surface and the occupant, this micro-
20 climate having a positive effect on the mental and physical fitness of the occupant.

DE 198 51 979 C2 discloses a vehicle seat, in which, in order to set a comfortable seat climate, a control unit
25 is provided which is connected on the input side to a temperature sensor for recording the temperature of the seat surface, the "integral sensor", and a moisture sensor, and is also connected on the output side to electric switching circuits of a seat heater and seat
30 ventilating system. The control unit is additionally connected on the input side by an outside temperature sensor for measuring the ambient temperature. A temperature adjusting system is integrated in the control unit and adjusts the surface temperature of
35 seat cushion and backrest cushion to a predetermined desired value by means of the seat heater and seat ventilating system. In this case, the desired value is corrected in the control unit as a function of the

temperature value supplied by the outside sensor. The correction here can take place in such a manner that, at an outside temperature of below 20°C, the desired value is set to, for example, 36°C, and at an outside
5 temperature of above 20°C, the desired value is lowered to, for example, 35°C. With this means of influencing the temperature which is to be adjusted at the seat surface, the seat user's perception of temperature depending on the time of year is taken into account.

10

The invention is now based on the object of indicating a method for adjusting the temperature of a motor vehicle seat, comprising a seat ventilating system and a seat heater, to a predetermined desired value T_{des} ,
15 in which the temperature T_s of the motor vehicle seat is detected in the region of the seat surface by a first temperature sensor and the outside temperature T_a is detected by a second temperature sensor, which ensures, for an occupant, a permanently comfortable,
20 warm and dry micro-climate between him and the seat surface.

The object is achieved by a method for adjusting the temperature of a motor vehicle seat, comprising a seat
25 ventilating system and a seat heater, in accordance with the features of patent claim 1.

According to the invention, in order to adjust the temperature T_s of a seat, a seat ventilating system is
30 switched off below a first temperature threshold T_{a1} for the outside temperature T_a , and a seat heater is switched off above a second temperature threshold T_{a2} for the outside temperature T_a . At low outside temperatures T_a (below the first temperature threshold
35 T_{a1} the adjusting system operates in "winter mode"), the temperature T_s of the seat is therefore set only by the seat heater and without the seat ventilating system whereas, at high outside temperatures T_a (above the

second temperature threshold Ta_2 the adjusting system operates in "summer mode"), the temperature T_s of the seat is set only by the seat ventilating system and without the seat heater. In the temperature interval
5 for the outside temperature T_a between the two temperature thresholds Ta_1 and Ta_2 , both the seat heater and the seat ventilating system can generally be used to adjust the temperature T_s of the seat. Experiments at low outside temperatures T_a show that
10 when seat ventilating system and seat heater are activated in parallel by an occupant, a cool air draft is felt at least in the upper body region. A large portion of the air fed into the motor vehicle seat by the seat ventilating system disappears from the
15 backrest of the motor vehicle seat via the shoulder region of the occupant. The dry air supplied absorbs some of the moisture from the occupant's skin surface, resulting in an unpleasantly cool sensation for the occupant. A sensation which is perceived by the
20 occupant as being entirely positive during summer weather conditions proves problematic at lower outside temperatures T_a . If the supply of air is constricted, the cool sensation is perceived as being no longer so negative. During winter mode without use of the seat
25 ventilating system, the occupant no longer has the unpleasantly cool sensation, and the occupant obtains an unlimited pleasant sensation. At higher outside temperatures T_a , with the seat heater and seat ventilating system operating together to adjust the
30 temperature T_s of the seat, sweating which is perceived as being unpleasant by the occupant starts. The best well-being for the occupant is obtained if the seat heater is not used in the summer mode. With the present method, comfortable cushion temperatures which lie in
35 the region of the normal skin temperatures are achieved in winter and in summer. The clothing and the skin of the occupant remain dry even under extreme climate conditions. A permanently comfortable, warm and dry

micro-climate is achieved between the seat surface and the occupant.

In one refinement, the value for the first temperature threshold T_{a1} is set to be equal to the value for the second temperature threshold T_{a2} . In particular, this common value is approx. 18°C . This makes it possible to completely omit a transition region permitting a parallel use of seat heater and seat ventilating system, as a result of which the adjustment of the temperature T_s of the seat is considerably simplified. In order to set the temperature T_s of the seat, use is made, depending on the outside temperature T_a , in other words in summer or in winter mode, of only the seat ventilating system or the seat heater.

Further advantageous refinements of the invention are reproduced in the subclaims.

The invention is explained in more detail in the single figure with reference to a number of exemplary embodiments, the figure showing a detail from a block circuit diagram for adjusting the temperature T_s of a motor vehicle seat comprising a seat ventilating system and a seat heater.

According to the figure, in the case of a method for adjusting the temperature T_s of a motor vehicle seat to a predetermined desired value T_{des} which can be set via a control device (not illustrated further), the temperature T_s of the seat is detected in the region of a seat surface (not illustrated further) by a first temperature sensor 2 and is compared with the desired value T_{des} . In addition, the outside temperature T_a is measured with a second temperature sensor 4 and is compared with a threshold value T_{ax} for the outside temperature T_a .

The deviation $T_{des}-T_s$ between the predetermined desired value T_{des} and the temperature T_s of the seat is processed by a first controller 6 for a seat heater 8 or by a second controller 10 for a seat ventilating system 12. Either the seat heater 8 is set in accordance with an output variable of the first controller 6 or the seat ventilating system 12 is set in accordance with an output variable of the second controller 10 as a function of the switching position of a switch 14 with a temperature-dependent switching function.

The temperature-dependent switching function of the switch 14 is configured in such a manner that, below a predetermined threshold value T_{ax} for the outside temperature T_a , a "winter mode", only the seat heater 8 is set with the adjusting system via the first controller 6. The seat ventilating system 12 is switched off in winter mode. Above the predetermined threshold value T_{ax} for the outside temperature T_a , a "summer mode", only the seat ventilating system 12 is set with the adjusting system via the second controller 10. The seat heater 8 is switched off in summer mode. In tests, a temperature value of approximately 18°C has proven worthwhile as the threshold value T_{ax} . A delimitation between winter and summer mode at this threshold value T_{ax} for the outside temperature T_a is perceived as being particularly pleasant by occupants. The threshold value T_{ax} may be varied as a function of individual perception. Furthermore, by deactivating the adjusting system, a manual actuation of seat heater 8 and seat ventilating system 12 is ensured.

In one exemplary embodiment (not illustrated further), the threshold value T_{ax} for the outside temperature T_a is divided into a first temperature threshold T_{a1} and a second temperature threshold T_{a2} with T_{a1} smaller than T_{a2} . The seat ventilating system 12 is switched off

below the first temperature threshold T_{a1} , and the seat heater 8 is switched off above the second temperature threshold T_{a2} . The winter and summer mode is separated by the temperature interval between the two temperature thresholds T_{a1} and T_{a2} in which a mixed mode is possible. In the temperature interval, seat heater 8 and seat ventilating system 12 can be used in parallel for adjusting the temperature T_s of the seat in order to improve the seating comfort for the occupants.

However, an individual operation of seat heater 8 and seat ventilating system 12 is also possible in this temperature interval bounded by the temperature thresholds T_{a1} and T_{a2} .

In the exemplary embodiment illustrated in the figure, the value for the first temperature threshold T_{a1} is therefore selected to be equal to the value for the second temperature threshold T_{a2} as a special case.

The predetermined desired value T_{des} for the temperature T_s of the seat has a value in the temperature range between 32.5°C and 35.5°C which corresponds to the individual well-being of the occupant and can be set individually. Irrespective of the outside temperature T_a , occupants in each case prefer a narrow temperature range for the temperature T_s of the seat, which they perceive as being pleasant. This generally lies in the given temperature range of between 32.5°C and 35.5°C and is essentially independent of summer and winter mode.

In a further refinement of the method, the temperature T_s of the seat can be adjusted to an upper desired value T_{desu} below the first temperature threshold T_{a1} for the outside temperature T_a , and the temperature T_s of the seat can be adjusted to a lower desired value T_{desl} above the second temperature threshold T_{a2} for the outside temperature T_a , the lower desired value

Tdesl being smaller than the upper desired value Tdesu. Both desired values Tdesl and Tdesu lie in the temperature range between 32.5°C and 35.5°C. Account is therefore taken of the personal finding that in summer
5 mode a somewhat cooler temperature Ts of the seat is preferred than in winter, as a result of which a freshening effect is obtained.

10 With the indicated method, the occupant is provided with a comfortable micro-climate in the seat region which to the greatest possible extent prevents unpleasant sensations in terms of feelings with regard to the thermo-physiological seating comfort.

DaimlerChrysler AG

Patent Claims

5 1. A method for adjusting the temperature T_s of a
motor vehicle seat, comprising a seat ventilating
system (12) and a seat heater (8), to at least one
predetermined desired value T_{des} , in which the
temperature T_s of the seat is detected in the region of
10 a seat surface by a first temperature sensor (2) and
the outside temperature T_a is detected by a second
temperature sensor (4), characterized in that the seat
ventilating system (12) is switched off below a first
temperature threshold T_{a1} for the outside temperature
15 T_a , and the seat heater (8) is switched off above a
second temperature threshold T_{a2} for the outside
temperature T_a .

2. The method as claimed in claim 1, characterized in
20 that the value for the first temperature threshold T_{a1}
is equal to the value for the second temperature
threshold T_{a2} .

3. The method as claimed in claim 1, characterized in
25 that the predetermined desired value T_{des} for the seat
temperature T_s has a value in the temperature range
between 32.5°C and 35.5°C.

4. The method as claimed in claim 1, characterized in
30 that the predetermined desired value T_{des} for the
temperature T_s of the seat is set as a function of the
outside temperature T_a .

5. The method as claimed in claim 1, characterized in
35 that the temperature of the seat T_s is adjusted to an
upper desired value T_{desu} below the first temperature
threshold T_{a1} for the outside temperature T_a , and is
adjusted to a lower desired value T_{desl} above the

P036819/WO/1

- 9 -

second temperature threshold Ta_2 , the lower desired value T_{desl} being smaller than the upper desired value T_{desu} and both lying in the temperature range between 32.5°C and 35.5°C .

DaimlerChrysler AG

Abstract

In the case of a method for adjusting the temperature T_s of a motor vehicle seat, comprising a seat ventilating system (12) and a seat heater (8), to a predetermined desired value T_{des} , in which the temperature T_s of the seat is detected in the region of a seat surface by a first temperature sensor (2) and the outside temperature T_a is detected by a second temperature sensor (4), the seat ventilating system (12) is switched off below a first temperature threshold T_{a1} for the outside temperature T_a , and the seat heater (8) is switched off above a second temperature threshold T_{a2} for the outside temperature T_a . By these measures, an occupant is provided with a comfortable micro-climate in the seat region for his/her well-being.

Figure



P036819/WO/1

1/1

